

Residential Pandect

Manufactured in:

New Zealand

Standard Compliant:

AS 1735.14

Application:

Residential use only

Installation:

External only

Drive system

Oil hydraulic

Supply Voltage

240 volt 100watt

Travels:

1 meter maximum

Lift Speed:

0.02mt / second

Lifting Capacity:

250kg

Lift Construction:

The main support frame and deck frame, are constructed from steel. These components are then sandblasted and hot zinc sprayed for maximum corrosion resistance.

The deck and entry ramp is manufactured from 3mm thick aluminium tread plate.

Deck Size:

1000mm x 1200mm

Deck Configuration:

Through entry / exit

90 degree angle entry / exit models

Electrical Features

The control panel has been designed to make the controls simple to operate.

Security Key - when the key is in the "off" position the lift is immobilised.

Up Button - When this button is pressed the lift will rise.

Down Button - When this button is pressed the lift will travel to the ground.

Emergency Stop - If this button is pressed, the lift will instantly stop.

Power of Operation - in the event of mains power failure the lift can complete 20 raise and lower operations on the back up battery.

Safety features:

An under deck protection system

An automatic fold up ramp is fitted to the entry end of the deck to prevent any likely wheelchair roll off.

A safety gate is fitted to all lifts as standard

The body side handrail is designed so that the user can slide their hand past the body work.

Back up battery

Maintenance:

We recommend that the lift be serviced at no greater intervals than 12 months. This will keep the lift in a safe and serviceable condition.

Warranty:

12 months on all parts and labour excluding misuse and/or malicious damage.